

## CENTRAL [MAIN] DISPLAY

---

### DESCRIPTION

---

The first 3 or 4 of the 6 characters are showing the number of the called ticket. 2 characters are showing the number of the expecting desk. Between these two values there is a LED-matrix which is able to show the direction in which the expecting desk is located. At the calling the display arouses the clients attention with a sound signal and with blinking. The number of the blinks can be set. The display can be ordered in 1, 2, 3,... 10 lined construction. At a new calling the datas of the previous ticket will jump down with one line. The newest call is always displayed in the first line. The display is able to visualise arabic and ciril characters too.



### TECHNICAL DATAS

---

Height:	150 mm per line
Width:	530 mm
Depth:	35 mm
Mass:	1 kg per line
Power supply:	12V=1A per line

### ATTRIBUTES

---

- 3 or 4 characters long are the ordinal numbers, one character for the direction (optional) 2 characters for the number of the expecting desk
- Extra brilliancy
- Adjustable blink speed and blink number (at client calling)
- Adjustable brilliancy
- Adjustable minimal time of displaying (in case of large turn-overs and less displays)
- Adjustable maximal time of displaying (in case of long term cases)
- Handling of new cases:
  - always in the top line,
  - in the actually free line.
- The central (main) displays can be ordered into groups and we can set which desk should work with which display and with which direction settings